



WTP1 PETROLATUM PASTE

DESCRIPTION

WRAPTITE WTP1 Paste is a single component, rust inhibiting, petrolatum coating, filler and lubricant

USES

WRAPTITE WTP1 Paste may be used as a primer underneath petrolatum tape systems to enhance corrosion protection and improve adhesion of petrolatum tapes. WTP1 Paste may also be used as a filler around bolts or gaps on flanges and couplings, as a stand alone corrosion protection coating or in areas where a rust inhibitive, non drying coating or lubricant is needed.

ADVANTAGES

Conforms to irregular surfaces. Can be applied to cold/wet surfaces. WTP1 Paste can be used to encapsulate lead based paints. Applicator safe, WTP1 Paste contains no solvents. It can be applied to marginally prepared surfaces and has a high melting point.

APPLICATION

All surfaces to be applied with WTP1 Paste should be completely clean. Remove all possible moisture, loose rust, mill scale, old coatings, dirt or other foreign matter with rags and by hand tool cleaning in accordance with SSPC-SP2 or by power tool cleaning in accordance with SSPC-SP3. Apply by hand or brush. As a primer apply at a coverage rate between 150-200 square feet per 6.6 lb can. As a filler or lubricant, apply as needed. WTP1 does not need any drying time or cure time before application of WTP1 Tapes.

GENERAL PROPERTIES

Total Thickness.....	varies
Composition.....	petrolatum and inert fillers
Cathodic Protection.....	excellent with petrolatum tape
Dielectric Strength.....	100 volts per mil
Normal Application Range.....	-30° F to 160° F
Normal Service Range.....	-30° F to 175° F

CHEMICAL RESISTANCE

Hydrocarbons.....	poor
Salts, bacteria, acids and alkalis.....	excellent

STANDARDS/SPECIFICATIONS

WTP1 Petrolatum Tape and WTP1 Paste meet or exceed AWWA C217 Standards

PACKAGING

WTP1 Petrolatum Paste is packaged 3 cans per box (6.6 lbs per can)
Shipping weight approximately 20 lbs per case